

TECHNICAL SPECIFICATIONS

Electronic Ballast for T8 Lamps type 2x18W/2x36W



Electronic built-in ballasts

- Suitable for luminaries safety class I
- Slim and compact shape
- Metal casing, side mounting possible

AC and DC operation

- Stabilized output power
- Low power losses
- Energy saving

Features

- Warm start according to the lamp performance standards
- EOL switch off
- Flicker less light

EMC requirements


- RFI conform up to 300MHz
- Power factor >0,96, low harmonics
- Immunity according standard

Lifetime

- > 50 000 h

Approvals

- ENEC, CE



ELECTRONIC BALLAST 2X18W/ 2X36W

TYPE	Dimensions/ mm			ta / °C	tc / °C	λ	TYPE	Lamp power (W)	Voltage AC 50-60 HZ (V+/-10%)	AC Voltage range (V AC)	AC Mains current (A)	Input DC voltage range (V DC)	OUTPUT Voltage (V)
	L	W	H										
2x18W	230 mm	40mm	28mm	-15+50°C	65 °C	0,98	T8	2X16W	220-240	198-264	0.18-0.15	198-264	350
2x36W	230 mm	40mm	28mm	-15+50°C	65 °C	0,98	T8	2X30W	220-240	198-264	0.32-0.29	198-264	350